




## LC Adapter



### Applications

- ◆ Telecom network
- ◆ CATV network
- ◆ Ethernet network
- ◆ Optical communication equipment

### Specifications

Item	Insertion Loss	Mechanical resistance	Repeatability	Operating Temperature
SM/PC	≤0.2dB	100-300g	<0.2dB(1000times)	-40℃ ~ +80℃
SM/APC	≤0.2dB	100-300g	<0.2dB(1000times)	-40℃ ~ +80℃
MM/PC	≤0.2dB	100-300g	<0.3dB(1000times)	-40℃ ~ +80℃

### Ordering Information:

Item	Mounting	Sleeve Material	Adapter Material	Colour
SM/PC Simplex	2 Flange	Zirconia Ceramic	Plastic	Blue
SM/PC Duplex	2 Flange	Zirconia Ceramic	Plastic	Blue
SM/APC Simplex	2 Flange	Zirconia Ceramic	Plastic	Green
SM/APC Duplex	2 Flange	Zirconia Ceramic	Plastic	Green
MM/PC Simplex	2 Flange	Ceramic/phosphor Bronze	Plastic	Beige
MM/PC Duplex	2 Flange	Ceramic/phosphor Bronze	Plastic	Beige



HONGKONG DONGWE TECHNOLOGIES CO.,LTD

香港东为科技有限公司

www.dongwe.cn

